



in

0

Ultrasun i8 Revive | Shape | Tan



View on our website

Standard equipped with



*Part of Full Audio Module

Additional options



** Maintain 10-15 cm clearance around the device for air circulation.

Lamp Specifications UV3 - Hybrid

Top Lamps:

36 x Sunfit XXL3 200W E-Tronic | 200 cm 12 x Sunfit CollaTan XXL3 200W E-Tronic | 200 cm Max. session time: 20 minutes

Any queries? Please call Helionova on 01603 789 010

Technical and Electrical Specifications

	THREE PHASE	SINGLE PHASE
Socket requirement:	32A/phase TPN&E	63A
Socket type:	Female Commando Socket	Female Commando Socket
Trip size:	32A/phase - C-type	50A - C-type
Power consumption:	9,400W (10,400W with airco)	9,400W (10,400W with airco)

Ventilation:

1 x 100 mm

Air extraction hose:


included


Weight and Dimensions

All dimensions in mm. Between brackets in inches.



Net weight: 250 kg Net weight + airco: 290 kg







Hyperion House, Alston Road Norwich, Norfolk, NR6 5DS United Kingdom 01603 789010 sales@helionova.co.uk helionova.co.uk



© 2025 Ultrasun International B.V. Product images may differ slightly from reality. Changes in specifications and design as well as printing and typographical errors are reserved.