



GARDASUN SUNSHINE 7000

TECHNICAL DETAILS

| | |
|-------------------|--|
| Total Lamps | 42 x Sunfit XL3 200W E-Tronic 190 cm |
| Power Consumption | ± 7,300 W |
| Power Supply | 50 Amps single or 16 Amps per phase TPN&E |
| Breaker | Type C Breaker |
| Weight | 235 Kg |
| Colour Options | Ice Blue Metallic <i>(Subject to availability)</i> |

FEATURES



Solar
Control



Top
Cooler

Changing Cubicle also available.

DIMENSIONS (OPEN)



Length = Door open dimension
Width = Door closed dimension
Height = Floor to ceiling

VENTILATION

The ventilation output is 500 cubic metres of air per hour.

Provision must be made for general room ventilation.

**ANY QUERIES? PLEASE CALL
HELIONOVA ON 01603 789 010**

ELECTRICAL REQUIREMENTS

Three Phase Supply

| | |
|--------------------|---|
| Socket Requirement | 16 amps per phase TPN&E. Female commando socket |
| Trip Size | 16 amps per phase C Type |

Single Phase Supply

| | |
|--------------------|--------------------------------|
| Socket Requirement | 63 amp. Female commando socket |
| Trip Size | 50 amp. C Type |

Each machine will have a male commando plug fitted with a minimum of 2.5m flex. If position of female socket requires a longer flex, please inform us prior to installation.



Changes in prices, technical specifications and design are reserved | 01-01-24 | V1