



# ULTRASUN SUNBURST 4000/3 MAGNUM

## TECHNICAL DETAILS

|                   |  |
|-------------------|--|
| Top Lamps         | 20 x Sunfit VRX3 140W E-Tronic   150 cm                |
| Base Lamps        | 18 x Sunfit VX3 160W E-Tronic   176 cm                 |
| Facial Lamps      | 2 x Sunfit WL 500W + 1 x Sunfit WL 1500W               |
| Power Consumption | ± 8,200 W  |
| Power Supply      | 50 Amps single or 16 Amps per phase TPN&E              |
| Breaker           | Type C Breaker   |
| Weight            | 295 Kg   |
| Colour Options    | Sunny Silver Metallic <i>(Subject to availability)</i> |

## FEATURES



Lumax  
Control



Body  
Cooler



Facial  
Lamps



Air  
Extraction  
Hose

## DIMENSIONS (OPEN)



Dimensions LxWxH of the sunbed with the canopy open.

## VENTILATION

The ventilation output is 1700 cubic metres of air per hour.

2 x 20cm diameter flexible ducts are fitted to the rear of the machine. The ducts can be fitted into a ventilation system or vented out to atmosphere providing this is not further than 3 metres from the sunbed.

**ANY QUERIES? PLEASE CALL  
HELIONOVA ON 01603 789 010**

## ELECTRICAL REQUIREMENTS

### Three Phase Supply

|                    |   |
|--------------------|---|
| Socket Requirement | 16 amps per phase TPN&E. Female commando socket |
| Trip Size          | 16 amps per phase C Type                        |

### Single Phase Supply

|                    |                                |
|--------------------|--------------------------------|
| Socket Requirement | 63 amp. Female commando socket |
| Trip Size          | 50 amp. C Type                 |

Each machine will have a male commando plug fitted with a minimum of 2.5m flex. If position of female socket requires a longer flex, please inform us prior to installation.



*Changes in prices, technical specifications and design are reserved | 01-01-24 | V1*