

PRIVACY PERFECTED

Changing Cubicle



MANUAL

WARNING: PLEASE READ THIS CAREFULLY

- Read this user manual before use.
- When opening up the sunbed or when replacing the lamps always remove the plug from the wall socket.
- This device needs to be connected to an electric socket with earth bonding.
- In case of a repair, maintenance or replacing of parts you need to make sure that your Ultrasun equipment is always provided with original Ultrasun parts to meet with the legal standards. In every other case the guarantee is invalid and we are in no case liable or responsible.
- For assembling instructions or technical information of the matching sunbed, please read the user manual of the specific sunbed.
- This changing cubicle is meant as a complement for the Ultrasun E7/E6/E5 and may therefore not be used for any other purpose.



Explaining the icons



Remove the plug from the wall socket when working on the sunbed.



Attention: dangerous electrical voltage.



Have a specialized fitter fix, repair or work on the sunbed



Many parts can be recycled, so keep them separate and do not dispose of them.



Attention: danger, read the instructions carefully and follow the directions.



Content

WARNING.....	2
CONTENT.....	3
TECHNICAL INFORMATION	3
ASSEMBLING THE CHANGING CUBICLE	4
DRAWINGS	6
TOPVIEW.....	10
DIMENSIONS CUBICLE E-SERIES.....	10
DECLARATION OF CONFIRMITY.....	11
CONTACT AND IDENTIFICATION.....	12

You have just chosen for a product from the Ultrasun range.

You have made an excellent choice.

By this purchase you have chosen for a product which has been carefully manufactured from high quality parts which have been tested completely and have been checked fully after manufacturing. We advise you to carefully read through this user manual so you can use the sunbed safely and with many years of pleasure.

During the development of our professional sunbeds, the specific desires of our customers have been taken into account. If you still have questions about or suggestions for our sunbeds, please do not hesitate to contact us.

Please check if the serial number plate at the back side of this user manual resembles the serial number plate at the back of the sunbed.

Ultrasun spends a lot of time and attention on the development and improvement of the delivered products. Ultrasun holds the right to make changes without informing you previously.

We hope you enjoy your purchased sunbed.
The Ultrasun team.






















Technical Information

SUNBED TYPE	CHANGING CUBICLE E-SERIES
Power supply:	230 Volt + PE
Power mirror circa:	3 Watt
Weight circa:	100 Kg (135 Kg with box)

Assembling the Changing Cubicle E5,E6 and E7

Check all components are included in the package :

 A 6M1041 2x	 B 6M1042 2x	 C 6M0995 2x	 D 6M0992 2x	 E 6M0998 1x
 F 1x	 G 2x	 H 1x		
 I 6M0931 1x	 J 6M0929 1x	 K 6M0991 1x		
 L 2x	 M 3x	 N M8 12x	 O M8 26x	
 P M8x25 15x(I9=16x)	 Q 3,9x19 10x	 R 6M1046 1x	 S M8x55 2x	

Note : The door does not have a vaulted part but also consists of a flat outer plate, just like the other parts.

Note : The brackets A, B, C, D and E are labeled with a sticker mentioning: 'THIS PART TO MACHINE'. This means that this side of the bracket must be directed towards the cabin or stand-up device (so NOT to the 'visible' outside of the mounted appliance). Please remove these stickers from the brackets before using them!

First assemble the Ultrasun E7/E6/E5; the sunbed to which the changing cubicle needs to be attached. How to assemble the Ultrasun E7/E6/E5 is described in the user manual which is delivered with the sunbed. Do not place the door part yet, place the topcooler but do not fasten it with the screws (do not place the cap nuts).

Fig.1 : To assemble the changing cubicle to the sunbed, the shackles (A) and (B) need to be assembled like indicated. The drawings “detail A” and “detail B” show the right position. (Attention: shackle (A) can be recognised by the slotted hole). Bolt (P) and nut (N) have been accentuated with exclamation marks in the detail of Fig. A. For now, these should not be fastened.

To assemble the top two shackles (these are situated on both sides under 1 support of the topcooler), first the “half” of a nut needs to be removed from this place. See Fig. 6 (i8) or Fig. 7 (i9) for the right positioning. After assembling the shackles (A and B) place the door part of the Ultrasun and tighten the cap nuts of the topcooler.

Fig.2 : First assemble shackle (R) and the adjustable foot under part (H) and fasten the two connecting brackets (C) and adjustable foot (M) like indicated in part (G). Then place part (H), with the mirror on the inside, between the shackles (A). After that, place part (G) between shackles (B).

Fig.3 : Under the last solid part (G) first assemble the adjustable foot part and then it can be fixed between the shackles (C). Mount the assemble shackle (R) together with rotation plate (D) with a ring (O) and a nut (N) under part (G), the bracket with the end-stop (E) is fixed on top of part (G) together with bracket (D).

Fig.4 : On the other side of plate (E) the connecting pipe (K) is mounted with distance piece (L), a bolt (S) and a ring (O), this should also be done on the other side, but there should be first placed a nut (N). The door part (F) can now be placed between the two brackets(D).

Fig.5. Turn the door inwards and fix the parts (I) and (J) like indicated. Both plates have to be fixed with screws (Q) (every plate needs 5 screws).

Attention: It must be possible for the door to be opened inwards!



Turn the adjusting foots (M) in or out so the cubicle stands up straight and the door closes properly. Finally tighten bolt (P) and nut (N). Make sure to secure all screws / nuts.
If the cubicle slides on a smooth surface we advise you to change the adjusting bases to ones that can be fixed to the floor.

The lighting in the door should be connected to the RGB connector underneath the bottom plate (or vibraplate) from your E7/E6/E5. The lighting from the mirror need to be connected to the cooling pillar.



Do not just throw discarded parts or wrapping in a scrap box but work them up separately, because many parts can be recycled.






Fig.1





Fig.2







Fig.4






Fig.5

Topview



Dimensions

LxBxH Changing Cubicle with E7/E6/E5:
209 x 165 x 227 cm



DECLARATION OF CONFORMITY

Directive 2014/35/EU and 2014/30/EU

We, **Ultrasun International BV**
Granaatstraat 6
7554 TR HENGELO, Holland

declare that this Ultrasun Changing Cubicle E-Series is in conformity with the actual version of the following normative documents:

Applied harmonized Standards:

Safety: EN 60335-1
Safety: EN 60335-2-27
EMC: EN 55014-1 and EN 55014-2
EMC: EN 61000-3-2 and EN 61000-3-3

following the provisions of the following directives:

IEC-Directives: Low Voltage Directive
2014/35/EU
Electromagnetic Compatibility Directive
2014/30/EU

Issued by:



J.W.S Fabels
CEO Ultrasun International
Hengelo, August 2016

DISCLAIMER

Ultrasun pays close attention to the quality of its products. This also applies to the information in this user manual. Ultrasun reserves the right to change the content of this manual at any time. Though Ultrasun strives to always display the correct texts and images in her manuals, errors can occur. We cannot be held responsible for any errors in writing or printing. We kindly ask you to report any discrepancy using the contact details at the back of this user manual. Thank you.



Scheme Sheet is
supplied separately